

XTREME POWER CONVERSION G90

Online UPS // 208/230VAC

For more information, visit www.xpcc.com/g90



Deliver clean and continuous power to IT equipment during power disturbances

The G90 revolutionizes power protection by delivering unprecedented operating efficiency, wattage density, and lower energy usage. Built with online double conversion technology, the G90 offers 0.9 output power factor and 98% efficiency in ECO mode which means you achieve the highest Power Usage Effectiveness (PUE) with the lowest utility power consumption.

PRODUCT SNAPSHOT

- › Available models: 1000VA, 2000VA, 3000VA
- › Rack, tower, or wall mount
- › Online double conversion, 98% efficiency in ECO mode
- › 0.9 output power factor
- › Compact 2U rack space
- › CE, FCC A, EN 61000, IEC/EN 62040 listings
- › 2 years electronics, 2 years battery warranty

FEATURES

0.9 output power factor—more wattage for high density loads. Provides up to 28.5% more real power than other lower power UPS technologies (0.7PF)

98% efficient operation—high efficiency ECO mode lowers energy consumption

Online double conversion—the G90 provides the highest level of power protection for critical electronics

Smart LCD display—vital monitoring and precise information from the front panel

Multiple communications capability—RS-232, USB and Web/SNMP

Programmable power management outlets—easily and independently control load segments

Hot Swappable—Internal battery trays are hot swappable for quick replacement

Fast battery recharge—typically less than 4 hour to recharge

Almost infinite scalable runtime—each battery pack has its own charger

XTREME
Power Conversion®

Protect your business.

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/g90

MODEL NUMBER		G90-1000	G90-2000	G90-3000
INPUT	Capacity	1000VA (900W)	2000VA (1800W)	3000VA (2700W)
	Voltage	160–290VAC		
	Frequency	50/60Hz auto sensing		
	Detachable AC power cord	6 ft, IEC C14 to IEC C13	6 ft, IEC C20 to IEC C19	
OUTPUT	Voltage	200/208/220/230/240VAC		
	Waveform	Pure sine wave		
	Frequency	50/60Hz auto sensing (line mode); 50/60 ± 0.02Hz (battery mode)		
	Power factor	0.9		
	Voltage regulation	± 2%		
	Crest factor	3:1		
	Outlets	(6) IEC C13	(8) IEC C13	(1) IEC C19 + (8) IEC C13
	Overload protection	150% for 30 sec; > 150% for 300 ms		
	Efficiency	98% ECO mode, ≥ 92% online mode		
BATTERY	UPS battery quantity and size	(3) 12V 9AH/36VDC	(6) 12V 9AH/72VDC	
	UPS/EBP charge current	1A (3 stage charger)		
	EBP battery quantity and size	(6) 12V 9AH/36VDC	(12) 12V 9AH/72VDC	
PHYSICAL	UPS dimensions (W x D x H)	440 x 430 x 86.5 mm (17.3 x 16.9 x 3.4 in)	440 x 690 x 86.5 mm (17.3 x 27.2 x 3.4 in)	
	UPS weight	16.2 kg (35.7 lbs)	28.1 kg (61.9 lbs)	29.2 kg (64.4 lbs)
	EBP dimensions (W x D x H)	440 x 430 x 86.5 mm (17.3 x 16.9 x 3.4 in)	440 x 690 x 86.5 mm (17.3 x 27.2 x 3.4 in)	
	EBP weight	24.0 kg (52.9 lbs)	46.0 kg (101.4 lbs)	
ENVIRONMENT	Temperature	0–40°C (32–104°F)		
	Humidity	0–95% non-condensing		
	Altitude	3500 m (11,500 ft) above sea level		
APPROVALS	CE, EN 61000, IEC/EN 62040			
WARRANTY	2 years electronics, 2 years battery			
COMMUNICATIONS INTERFACE	RS-232, USB, Web/SNMP (optional)			
INCLUDED IN BOX	User manual, rack mount brackets, tower pedestals, power cord, software CD, USB & SNMP cables			
AVAILABLE OPTIONS	Bypass distribution module (XBDM), power distribution module (XPDU), rail kit			

BATTERY RUNTIMES *(Runtimes are shown in minutes and will vary based on battery age and site conditions.)*

	UPS	+ (1) EBP	+ (2) EBP	+ (3) EBP	+ (4) EBP
Backup time*	Half/full	Half/full	Half/full	Half/full	Half/full
G90-1000 (0.8 PF load)	21/9	87/35	167/68	259/96	358/148
G90-1000 (0.9 PF load)	18/8	75/31	144/59	222/91	307/125
G90-2000 (0.8 PF load)	21/9	87/35	167/68	259/96	358/148
G90-2000 (0.9 PF load)	18/8	75/31	144/59	222/91	307/125
G90-3000 (0.8 PF load)	12/6	52/21	99/41	154/63	212/87
G90-3000 (0.9 PF load)	11/4	44/18	86/35	132/55	183/75

*For runtimes up to 18 hours, contact sales@xpcc.com.

X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2014 Xtreme Power Conversion Corporation. All Rights Reserved. G90.011 (Rev 10/20/14)

